

# LLB&L

**Locke Lord Bissell & Liddell, LLP**

Attorneys &amp; Counselors

3 World Financial Center  
New York, NY 10281  
Telephone: (212) 415-8600  
Fax: (212) 303-2754  
www.lockelord.com

Zachary D. Silbersher  
Direct Dial: (212) 415-8544  
Fax: (212) 303-2754  
zsilbersher@lockelord.com

**FAX COVER SHEET**

October 25, 2010

To:	Organization:	Fax Number:	Phone Number:
Atul Khare	US PTO	(571) 270-8608	(571) 270-7608

From:	Organization:	Fax Number:	Phone Number:
Zach Silbersher, Esq.	Locke Lord Bissell & Liddell LLP	(212) 303-2754	(212) 415-8544

Total Pages (including coversheet): 3 pages (including coversheet)

If you do not receive all pages, please call Ms. Bettina Miraglia at (646) 217-7443, or email her at bmiraglia@lockelord.com.

Proposed Amendment for Claim 1 of Patent Application No. 10/520,689

Subject: LLBL Reference No. 1004475.001US

Message: Please see attached.

This message is intended for the use of the individual or entity to which it is addressed, and may contain information that is privileged, confidential and exempt from disclosure under applicable law. If the reader of this message is not the intended recipient, or the employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited. If you have received this communication in error, please notify us immediately by telephone, and return the original message to us at the above address via the U.S. Postal Service. Thank you.

NY:1004475/001US:633603v1

To: Atul Khare

Tel: 571.270.7608

Fax: 571.270.8608

Application No. 10/520,689

Dear Examiner Khare:

In connection with the interview scheduled for Friday, October 29, 2010 at 1:20 p.m., application no. 10/520,689, below is a proposed amendment for claim 1.

Regards,

Zachary Silbersher

212.415.8544

\* \* \* \* \*

1. (Currently Amended) A method of denticulation of a concrete joint between a first and a second cast section,

assembling a form at the location of the concrete joint by attaching a formwork,  
casting a first cast section into the formwork,

removing the formwork prior to casting a second cast section,  
casting the second cast section,

wherein the formwork for the first cast section comprises a studded plate,  
wherein the studded plate has studs where the stud side wall inclination angle is

greater than 60° with respect to the surface of the studded plate,

wherein the studded plate has bridges or backs between the studs,

wherein the bridges or the backs comprise an area that is parallel to a plane  
comprising the tops of the studs and parallel to a plane comprising the surface of the studded  
plate, but is not within either of these planes and is within a plane that is between the plane  
comprising the tops of the stud and the plane comprising the surface of the studded plate.

wherein the ~~surface of the studded plate is vacant~~ area below the bridges or the  
backs of the studded plate is vacant,

wherein the studded plate has studs that are square, polygonal or round,  
wherein the studded plate has studs positioned in relation to each other in a pattern.